

# IRONWOOD CUT18 CROSS CUT SAW



## ADVANCED FEATURES

- 10 HP high torque IE3 motor
- Foot pedal saw activation - hands-free operation
- Easily adjustable rise and fall rate
- Enhanced blade guarding for operator safety
- Blade access door switch for safer blade changes
- Pre-drilled and tapped for TigerStop tables
- Available in plastics and metal configuration
- Optional equipment includes: dual hand controls, hydraulic cylinder upgrade, zero cutline back fence, side pressure clamp, machine tilt brackets, and infeed/outfeed tables.

The IRONWOOD CUT18 up-cut saw offers a safe and reliable, yet compact crosscutting solution. With a precision-ground table surface, this saw ensures absolute cutting accuracy while maintaining stability during heavy cutting operations. The CUT18 highlights enhanced safety guards and a powerful, high torque motor to handle even the heaviest cutting applications.

Technical Specifications	CUT18
Motor Horsepower	10 HP (7.5 kW)
Blade Size	18" (457 mm)
Arbor Size	1" (25.4 mm)
Cutting Depth Max	4" (101.6 mm)
Cutting Width Max	12" (304.8 mm)
Max Cycles per minute	45 CPM
Saw Speed	3200 RPM
Table Size	26" x 25.5" (660.4 x 647.7mm)
Working Table Height	34" (863.6 mm)
Dust Port Ø / CFM	4" (101.6 mm) / 450 CFM
Air Pressure Required	80-90 PSI
Machine Voltage	230V or 460V   3-Phase   60Hz.
Rated Current*	230V: 26.4A   460V: 13.2A
Start Current*	230V: 220A   460V: 110A
Machine Weight	900 lbs. (408 kg)
Packing Dimensions	37" x 33.25" x 53" (940mm x 845mm x 1346mm)



\*Non-Star Delta starter. Start-up amperages will exceed actual rated amperage draw.